

Duct -Split

Model	Indoor unit	HNME 3.2	HNME 5	HNME 10	HNME 12	
	Out door	HNCD 3.2	HNCD 5	HNCD 10	HNCD 12	
Nominal cooling capacity	Kcal/h	10000	15000	28.750	34150	
	K.Watt	11.600	17.400	33.500	39.700	
Nominal heating capacity	Kcal/h	10500	16600	22300	29350	
	K.Watt	12.163	19.343	27875	36680	
Cooling power input	K.Watt	3.0	4.4	8.17	12.35	
Heating power input	K.Watt	2.35	3.8	7.7	11.00	
Voltage	V*ph*Hz	380*3*50				
Refrigerant	R22					
Indoor unit	Fan Type	Centrifugal / Direct 3 Speeds				
	Air flow	M ³ /h	2200	3500	5500	8800
	External state pressures(mm)	M ³ /h	2200/10	3500/12	5500/10	8800/12
	Dimension	Height (mm)	230	350	60	60
		Width (mm)	1350	1225	115	156
		Depth (mm)	560	750	950	950
	Weight	Kg	36	54	85	110
Outdoor unit	Compressor type	Hermetic - Reciprocation				
	Rated running current	A	4.5-5.2	7.8-8	12-14	17-20
	Fan type /drive	Axial				
	Dimension	Height (mm)	1250	1250	1450	1450
		Width (mm)	860	860	1650	1650
		Depth (mm)	290	290	450	450
Weight	Kg	75	75	150	150	
Connection	Liquid (inch)	1/2(Flare)	1/2(Flare)	1/2(Brazing)	1/2(Brazing)	
Pipe size	Gaz (inch)	5/8(Flare)	3/4(Flare)	1 1/8 (Brazing)	1 1/8 (Brazing)	